§835.403

DOE Laboratory Accreditation Program for Radiobioassay; or,

(2) Determined by the Secretarial Officer responsible for environment, safety and health matters to have performance substantially equivalent to that of programs accredited under the DOE Laboratory Accreditation Program for Radiobioassy.

[63 FR 59683, Nov. 4, 1998, as amended at 72 FR 31926, June 8, 2007]

§835.403 Air monitoring.

- (a) Monitoring of airborne radioactivity shall be performed:
- (1) Where an individual is likely to receive an exposure of 40 or more DAC-hours in a year; or
- (2) As necessary to characterize the airborne radioactivity hazard where respiratory protective devices for protection against airborne radionuclides have been prescribed.
- (b) Real-time air monitoring shall be performed as necessary to detect and provide warning of airborne radioactivity concentrations that warrant immediate action to terminate inhalation of airborne radioactive material.

[63 FR 59683, Nov. 4, 1998]

§835.404 [Reserved]

§835.405 Receipt of packages containing radioactive material.

- (a) If packages containing quantities of radioactive material in excess of a Type A quantity (as defined at 10 CFR 71.4) are expected to be received from radioactive material transportation, arrangements shall be made to either:
- (1) Take possession of the package when the carrier offers it for delivery; or
- (2) Receive notification as soon as practicable after arrival of the package at the carrier's terminal and to take possession of the package expeditiously after receiving such notification.
- (b) Upon receipt from radioactive material transportation, external surfaces of packages known to contain radioactive material shall be monitored if the package:
- (1) Is labeled with a Radioactive White I, Yellow II, or Yellow III label (as specified at 49 CFR 172.403 and 172.436-440); or

- (2) Has been transported as low specific activity material (as defined at 10 CFR 71.4) on an exclusive use vehicle (as defined at 10 CFR 71.4); or
- (3) Has evidence of degradation, such as packages that are crushed, wet, or damaged.
- (c) The monitoring required by paragraph (b) of this section shall include:
- (1) Measurements of removable contamination levels, unless the package contains only special form (as defined at 10 CFR 71.4) or gaseous radioactive material; and
- (2) Measurements of the radiation levels, if the package contains a Type B quantity (as defined at 10 CFR 71.4) of radioactive material.
- (d) The monitoring required by paragraph (b) of this section shall be completed as soon as practicable following receipt of the package, but not later than 8 hours after the beginning of the working day following receipt of the package.
- (e) Monitoring pursuant to §835.405(b) is not required for packages transported on a DOE site which have remained under the continuous observation and control of a DOE employee or DOE contractor employee who is knowledgeable of and implements required exposure control measures.

[63 FR 59683, Nov. 4, 1998, as amended at 72 FR 31926, June 8, 2007]

Subpart F—Entry Control Program

§835.501 Radiological areas.

- (a) Personnel entry control shall be maintained for each radiological area.
- (b) The degree of control shall be commensurate with existing and potential radiological hazards within the area.
- (c) One or more of the following methods shall be used to ensure control:
 - (1) Signs and barricades;
 - (2) Control devices on entrances;
- (3) Conspicuous visual and/or audible alarms:
 - (4) Locked entrance ways; or
 - (5) Administrative controls.
- (d) Written authorizations shall be required to control entry into and perform work within radiological areas.